

## Specifications

Model	<u>G25L</u>	<u>HG25L</u>	<u>G25</u>	<u>HG25</u>	<u>G25DF</u>	<u>HG25DF</u>	<u>D25</u>	<u>HD25</u>
Tire Type	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic
Load Capacity	5000 lbs (2260kg)	5000 lbs (2260kg)	5000 lbs (2260kg)	5000 lbs (2260kg)	5000 lbs (2260kg)	5000 lbs (2260kg)	5000 lbs (2260kg)	5000 lbs (2260kg)
Service Weight	7870 lbs (3570 kg)	7870 lbs (3570 kg)	7870 lbs (3570 kg)	7870 lbs (3570 kg)	7870 lbs (3570 kg)	7870 lbs (3570 kg)	8160 lbs (3700 kg)	8160 lbs (3700 kg)
Free Lift	6.3 in (160 mm)	6.3 in (160 mm)	6.3 in (160 mm)	6.3 in (160 mm)	6.3 in (160 mm)	6.3 in (160 mm)	6.3 in (160 mm)	6.3 in (160 mm)
Max Fork Height*	130" (3302 mm)	130" (3302 mm)	130" (3302 mm)	130" (3302 mm)	130" (3302 mm)	130" (3302 mm)	130" (3302 mm)	130" (3302 mm)
Power Type	Spark Ignition, IC	Spark Ignition, IC	Spark Ignition, IC	Spark Ignition, IC	Spark Ignition, IC	Spark Ignition, IC	Diesel	Diesel
Fuel	LPG	LPG	Gasoline	Gasoline	Dual Fuel	Dual Fuel	Diesel	Diesel
Displacement	126.4 cu-in (2.065 liter)	203.1 cu-in (3.318 liter)	126.4 cu-in (2.065 liter)	203.1 cu-in (3.318 liter)	126.4 cu-in (2.065 liter)	203.1 cu-in (3.318 liter)	162.5 cu-in (2.663 liter)	203.1 cu-in (3.318 liter)
Rated Output HP/RPM	51.9/2700	67/2500	51.9/2700	67/2500	51.9/2700	67/2500	55/2300	67/2500
Max Travel Speed w/ Load	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.5 mph (18.5 km/h)	11.2 mph (18.0 km/h)	11.2 mph (18.0 km/h)
Lift Speed w/ Load	106.3 fpm (540 mm/s)	106.3 fpm (540 mm/s)	106.3 fpm (540 mm/s)	106.3 fpm (540 mm/s)	106.3 fpm (540 mm/s)	106.3 fpm (540 mm/s)	124.0 fpm (630 mm/s)	124.0 fpm (630 mm/s)
Overall Length (without forks)	100.6 in (2555 mm)	100.6 in (2555 mm)	100.6 in (2555 mm)	100.6 in (2555 mm)	100.6 in (2555 mm)	100.6 in (2555 mm)	100.6 in (2555 mm)	100.6 in (2555 mm)
Overall Width	45.3 in (1150 mm)	45.3 in (1150 mm)	45.3 in (1150 mm)	45.3 in (1150 mm)	45.3 in (1150 mm)	45.3 in (1150 mm)	45.3 in (1150 mm)	45.3 in (1150 mm)
Overall Height Fork Lowered	79.9 in (2030 mm)	79.9 in (2030 mm)	79.9 in (2030 mm)	79.9 in (2030 mm)	79.9 in (2030 mm)	79.9 in (2030 mm)	79.9 in (2030 mm)	79.9 in (2030 mm)
Right Angle Stack	107.1 in (3990 mm)	107.1 in (3990 mm)	107.1 in (3990 mm)	107.1 in (3990 mm)	107.1 in (3990 mm)	107.1 in (3990 mm)	107.1 in (3990 mm)	107.1 in (3990 mm)

\*Based on 130" Standard Upright (Model VM330)