

# UNICARRIERS<sup>®</sup>

## □ FORKLIFT □

# MXS Series



### Electric Counterbalanced Forklifts

48 Volt AC-Powered  
2700 - 4000 lbs. Capacities



# MXS Series Applications

---

Built to meet customer needs with dependable performance, durability and adaptability – backed by excellent customer service – The MXS series available in 3 and 4-wheel options are your choice when space is tight. Due to their compact design, amazing maneuverability and intelligent control systems, they are ideal for:

- Food and Beverage manufacturing and wholesale
- Fishing and fish processing
- Chemicals, textiles and rubber
- General and refrigerated warehousing and storage
- Machinery and heavy equipment
- Electric equipment and components

We can offer your business a total solution, whatever your shift pattern, application or environment.





# NEVER QUIT.

It defines our forklifts and the company that builds them.

Over the course of a century, the company known as UniCarriers took shape. As we grew and evolved into a US manufacturer with a global reach in nearly 100 countries worldwide, much has changed, but one thing hasn't: Our mission. UniCarriers is committed to providing you with the ultimate in reliability, performance, and value.

And that commitment can be seen in the MXS Series. The right choice when space is tight, their compact design, amazing maneuverability and intelligent control systems make them ideal for efficient handling in containers, trucks, drive-in racking and other cramped, fast-paced environments. They are also built to stand up to harsh, wet, dirty or dusty conditions. Add UniCarriers' legendary reliability, energy efficiency and durability — and you have the right forklift to move your products, and your business, forward.



## Up Your UpTime

Discover reliability features that cut downtime and keep your business up and running



## Comfort Zone

Your drivers and your entire operation will benefit from our comfort & productivity features



## Power & Performance

Reliable AC motors and controllers are only the beginning of our performance advantages



## Sweet Savings

The MXS series are designed to deliver you a low cost of ownership year after year after year



## Play It Safe

Safety is everybody's business, and these models are all business when it comes to safety



## Make It Yours

Already well appointed, the MXS series can be customized to meet your specific needs



To learn more, and find a dealer near you, visit [LogisnextAmericas.com/UniCarriers](https://LogisnextAmericas.com/UniCarriers)

# Up Your UpTime





### **Reduce Downtime with Self-Diagnostics**

To maximize uptime and maintain the performance levels of these durable trucks, we build easy servicing into their design. Integrated on-board diagnostics provide immediate truck status. It's intuitive dialogue display combined with accessible service history reduce troubleshooting time, so the unit is back in operation faster. Everything is done through a smart LCD panel. No handset device is needed.



### **Electromagnetic Brakes**

Fully electronic magnetic brakes require less servicing and offer greater energy efficiency. The electromagnetic parking brake standard does not require hand levers to release the brakes, helping to reduce maintenance costs and total cost of ownership.



### **Simplified Battery Maintenance & Replacement**

Fast-access battery compartment offers easy opening for maximum ventilation during charging and quick battery checks and maintenance. Fast battery compartment access speeds up servicing and exchanges.

# Comfort Zone



**You work smart,  
you work hard –  
why not work in  
comfort? All the  
amenities to make  
the workday fly by.**



### Improved Control and Productivity

Designed and engineered to perform, these 48-volt three- and four-wheel electrics work intuitively, tailoring their performance to your individual operator. Their sophisticated software analyzes behavior in real-time and automatically adjusts the truck's behavior for safe but productive performance. Driving and load handling is easier, steadier and more comfortable. Drivers feel the machine is totally in tune with them, so they are happy, confident and highly productive.



### Ideal Operating Space

Large, ultra-comfortable operating space has been enhanced to meet the needs of drivers of different shapes and sizes for fatigue-free operation. Spacious footwell provides additional comfort to operators of different sizes to enjoy a natural, ergonomic, foot position. Optimized pedal positioning encourages a more natural foot position for drivers of all sizes – short and tall included – to keep fatigue at bay. Quickly step and swing into and out of the spacious operator compartment.



### Superior Visibility

Thanks to its optimized mast, steering wheel, dashboard and counterweight design, the MXS series maximizes visibility to load, forks, front and rear wheels for safe, confident operation in tight spaces. Clear informative full-color display is easy to read from any angle (even in direct sunlight). It's ideally positioned for operator reference and doesn't reduce the truck's all-round visibility. From there, the inclined and narrow dashboard design allows clear forward, downward and side views without having to lean.



### Convenience at Your Fingertips

Optional touch sensitive fingertip controls are spring-loaded for a natural feeling and is gentle to the touch. Ergonomic controls include an adjustable armrest when selecting the optional fingertip controls. Interesting advances include a synchronization system for the steering knob, which automatically returns it to the correct 8 o'clock position whenever the truck straightens up – even if the wheel has been forced beyond its end stop.




### Control and Security

Sensitive Drive System (SDS) smooths start and stop movements, increases agility and adapts to the speed of operators' foot movements. Automatic parking brake with hill holds stops the truck automatically when the accelerator is not engaged and prevents rolling on ramps.



# Power & Performance

Highly Responsive,  
Highly Productive.



For greater productivity throughout the work cycle, the MXS Series' AC power system delivers responsive, precise control. The performance and durability of these UniCarriers' electric lift trucks is without question. It owes much to the expertise, advanced technology and strict quality standards applied by our ultra-modern production center. Faster acceleration, higher top travel speeds and infinitely variable lift/lower control mean more work is completed, faster.



**Sensitive Drive System**

Sensitive Drive System (SDS) smooths start and stop movements, increases agility and adapts to the speed of operators' foot movements.



**Responsive Drive System**

Responsive Drive System (RDS) adapts performance rapidly in reaction to speed of pedal operation, and helps ensure that travel movements, starts and stops are smooth.

**High Efficiency Motors**

High-efficiency motors offers a high RPM range for precise control when accelerating creating more torque at low speeds and reducing energy consumption. Intelligent curve control senses the angle of a turn and responds – automatically reducing speed early in the maneuver – helping to ensure stability and accurate, positive cornering.

**Benefits of Moving to Lithium-Ion Technology**

- Fast charging throughout the course of the shift during breaks allows the truck to stay charged when customers need it.
- Li-Ion Batteries are smart power solutions designed to communicate directly with the truck, resulting in increased efficiency and output.
- The Li-Ion solution is completely maintenance free, which can help reduce the overall cost of ownership



and the downtime associated with maintaining and caring for traditional lead acid batteries.

- Battery life expectancy of up to 3,000 full cycles (vs. 900 to 1,200 cycles in lead-acid batteries)
- No gas is produced during charging and no acid is contained in the battery as compared with conventional lead-acid batteries.

**Compensates for Load Weight**

A load-sensing hydraulic system automatically adjusts for weight, to maintain precise control. (In forklifts without intelligent hydraulics, lifting and lowering feels very different when the weight of the load is varied). In addition, there is electronic compensation for load weight when using different hydraulic functions simultaneously (via optional fingertip controls), so all mast movements remain consistent.



**Optimized Steering System**

The optimized steering system provides consistently smooth operations and maximum control regardless the speed or work intensity. Timesaving 360-degree steering option on 3-wheel models means the

operator keeps the truck in constant motion – saving seconds on every turn. >100-degree steering axle with dual-drive motors on 4-wheel models offers smooth 'on the spot' turning, with no initial 'push'. Advanced curve control coordinates the two front-wheel drive motors and rear steer axle motor to optimize turning speed during cornering which helps stabilize the truck during turns.

**Passive Sway Control**

During lifts, a passive sway control function, specified as standard, takes effect. This works by keeping the automatic parking brake open so mast sway energy is absorbed by the mass of the whole truck. Reduction of sway and twisting, as well as noise, is enhanced through strong mast design and a low-friction side-shift. As an option for lifts between about 78in/2m and 138in/3.5m meters (and standard for 138in/3.5m upward), hydraulic performance can be automatically adjusted for added operator comfort. A similar automatic system limits truck acceleration when lifting at these heights.

# Sweet Savings



Economical  
and Flexible



### **Lower Maintenance Costs**

The electromagnetic parking brake standard does not require hand levers to release the brakes, helping to reduce maintenance costs and total cost of ownership.



### **Pre-set and Programming Options**

Performance and efficiency can be optimized for each application through full programming, or by simply selecting one of the pre-set operating modes. Profits are maximized by achieving the right balance between output and total cost of ownership.



### **Built to Last**

As well as saving money daily with their low energy consumption, our lift trucks are able to reduce the total cost of ownership through features such as:

- Sealing of components against water and other contaminants
- Use of highly durable materials and designs
- 1,000-hour PM intervals

# Play It Safe





**Clearly Better**

Excellent visibility thanks to optimized mast, steering wheel, inclined and narrow dashboard and counterweight design, maximizes visibility to load, forks, front and rear wheels for safe, confident operation in tight spaces.



**Passive Sway Control**

Passive Sway Control dampens any elevated load motion above 138in/3.5m, by compensating with micro-chassis movements. Load-sensing hydraulic system automatically adjusts to the weight being handled, to maintain precise control. Intelligent curve control senses the angle of a turn and responds – automatically reducing speed early in the maneuver – helping to ensure stability and accurate, positive cornering.

**Stop. Stay.**

Presence Detection System+ includes automatic parking brake, hill hold and – if operator is not properly seated – prevention of travel and hydraulic movement. Automatic parking brake with hill holds stops the truck automatically when the accelerator is not engaged and prevents rolling on ramps.




# Make it Yours

Choose from a variety of options to customize your ride. If you don't see what you need, contact your authorized UniCarriers dealer for help.



## Smart and Durable

It's one of the most intelligent and durable trucks on the market today. Packed with features, it delivers the maneuverability, power and reliability you expect from UniCarriers. Modular design simplifies addition or replacement of parts, including overhead guard and cabin options.



## Protection From Falling Debris

Among many optional features available to match the truck with your application is a high visibility overhead guard. While its rear is reinforced with steel, the fully transparent front area has a robust polycarbonate structure with a glass layer to prevent scratches and discoloration.





## Adjust for Your Needs

Pre-set ECO and PRO modes can be selected for different drivers and tasks, or customized settings can be applied by service engineers.



## Here to Serve You

To help you choose the right model and configuration, and maintain its productivity, we have a dedicated network of dealers. With their specialist knowledge, wide experience and excellent service they will support you in every way to help maximize your profits.





**MAIN TRUCK SPECIFICATIONS - 3 WHEEL**

CHARACTERISTICS	1	Manufacturer's Name		UniCarriers	UniCarriers	UniCarriers	
	2	Model	Model designation	MXST14-2	MXST16C-2	MXST18C-2	
	3	Rated Load Capacity		2700 (1250)	3000 (1425)	3500 (1600)	
	4	Load Center	Distance	23.6 (600)	23.6 (600)	23.6 (600)	
	5	Power Type	Electric	Electric/48V	Electric/48V	Electric/48V	
	6	Operator Orientation		Seated	Seated	Seated	
DIMENSIONS	7	Tire Type	Front & rear	Solid Pneu.SE	Solid Pneu.SE	Solid Pneu.SE	
	8	Wheels	Number - front/rear (x=driven)	2x/1	2x/1	2x/1	
	9	Mast	Maximum fork height	in (mm)	129.5 (3290)	129.5 (3290)	129.5 (3290)
	10		Mast lowered (OHL)	in (mm)	83.7 (2125)	83.7 (2125)	83.7 (2125)
	11		Mast extended with LBR	in (mm)	170.7 (4335)	170.7 (4335)	170.7 (4335)
	12		Standard freelif	in (mm)	3.1 (80)	3.1 (80)	3.1 (80)
	13	Forks	Thickness & width & Length	in (mm)	1.4x3.9x5.9 (35x100x1150)	1.4x3.9x5.9 (35x100x1150)	1.4x3.9x5.9 (35x100x1150)
	14	Tilt Angle	Standard mast - fwd/back	degree	5/7.5	5/7.5	5/7.5
	15	Overall Dimensions	Length (to face of forks)	in (mm)	72.7 (1846)	72.7 (1846)	72.7 (1846)
	16		Width (standard tires)	in (mm)	42.9 (1090)	42.9 (1090)	42.9 (1090)
	17		Height - top of OHG	in (mm)	80.7 (2050)	80.7 (2050)	80.7 (2050)
	18		Height - top of standard LBR	in (mm)	48.0 (1220)	48.0 (1220)	48.0 (1220)
	19		Width - standard carriage	in (mm)	36.2 (920)	36.2 (920)	36.2 (920)
	20	Grade Clearance	Ramp breakover angle (with/without load)	%	3.7 (95)	3.7 (95)	3.7 (95)
21	Overhang	Front	in (mm)	13.5 (343)	13.5 (343)	13.5 (343)	
22	Turning Radius	Minimum outside	in (mm)	59.1 (1502)	59.1 (1502)	59.1 (1502)	
23	Min Right Angle Stack	1000 x 1200 mm pallets, crosswise / 800 x 1200 mm pallets, lengthwise	in (mm)	124.9 (3173) / 129.8 (3296)	124.9 (3173) / 129.8 (3296)	124.9 (3173) / 129.8 (3296)	
PERFORMANCE	24	Speed Maximum	Travel - loaded / unloaded	mph (km/h)	10.6 (16)	10.6 (16)	10.6 (16)
	25		Lift - loaded / unloaded	fpm (mm/sec)	0.55/0.62	0.52/0.62	0.46/0.62
	26		Lowering - loaded / unloaded	fpm (mm/sec)	0.56/0.56	0.56/0.56	0.56/0.56
	27	Drawbar Pull Maximum	Full load	lb (N)	3372 (15000)	3350 (14900)	3350 (14900)
28	Gradeability Maximum	Full load (with/without load)	%	27/35	27/35	26/35	
WEIGHT	29	Truck Weight	Empty, min. battery	lb (kg)	6150.9 (2790)	6538.9 (2966)	6957.8 (3156)
	30	Weight Distribution	Full load front/rear - min. battery	lb (kg)	8130.6 (3688) / 1106.7 (502)	8851.6 (4015) / 1214.8 (551)	9592.3 (4351) / 1333.8 (605)
	31		No load front/rear - min. battery	lb (kg)	3073.2 (1394) / 3077.7 (1396)	3071.0 (1393) / 3467.9 (1573)	3095.2 (1401) / 3866.9 (1754)
CHASSIS & WHEELS	32	Tire Size	Front	in	18x7-8	18x7-8	18x7-8
	33		Rear	in	140/55-9	140/55-9	140/55-9
	34	Wheelbase		in (mm)	52.0 (1320)	52.0 (1320)	52.0 (1320)
	35	Tread - Center of Tire	Front / rear (standard tires)	in (mm)	36.6/6.9 (930/174)	36.6/6.9 (930/174)	36.6/6.9 (930/174)
	36	Headroom	SIP to bottom pf OHG	in (mm)	35.7 (908)	35.7 (908)	35.7 (908)
	37	Counterweight Height		in (mm)	38.04 (966.36)	38.04 (966.36)	38.04 (966.36)
	38	Step Height		in (mm)	16.0 (407)	16.0 (407)	16.0 (407)
	39	Ground Clearance	Under mast	in (mm)	3.7 (95)	3.7 (95)	3.7 (95)
	40		Under frame, center of wheelbase	in (mm)	3.7 (95)	3.7 (95)	3.7 (95)
	41	Service Brake	Type		Electric	Electric	Electric
42	Parking Brake	Type		Magnetic	Magnetic	Magnetic	
43	Steering	On-demand		Electric	Electric	Electric	
DIN 320A 48V LINE	44	Traction Motor	Type / Rating (1-hour)	(kW)	AC / 2 x 5.5 kW	AC / 2 x 5.5 kW	AC / 2 x 5.5 kW
	45		Control type		AC	AC	AC
	46	Pump Motor	Type / Rating (5-minute)	(kW)	AC / 10 kW	AC / 10 kW	AC / 10 kW
BATTERY	47	Battery Compartment Size	W x H - Maximum	in (mm)	W: 33.5 (850) with spacers W: 40.0 (1018) w/o spacers H: 26.0 (660) with battery rollers H: 27.2 (690) w/o battery rollers	W: 33.5 (850) with spacers W: 40.0 (1018) w/o spacers H: 26.0 (660) with battery rollers H: 27.2 (690) w/o battery rollers	W: 33.5 (850) with spacers W: 40.0 (1018) w/o spacers H: 26.0 (660) with battery rollers H: 27.2 (690) w/o battery rollers
	48		L - Maximum	in (mm)	20.9 (532)	20.9 (532)	20.9 (532)
	49	Recommended Battery Size	W x H - Maximum	in (mm)	W: 32.7 (830) with spacers W: 39.6 (1006) w/o spacers H: 24.7 (627)	W: 32.7 (830) with spacers W: 39.6 (1006) w/o spacers H: 24.7 (627)	W: 32.7 (830) with spacers W: 39.6 (1006) w/o spacers H: 24.7 (627)
	50		L - Maximum	in (mm)	20.6 (522)	20.6 (522)	20.6 (522)
	51		Lead acid	Type	Lead acid	Lead acid	Lead acid
	52	Capacity	Minimum / Maximum	Ah/5h	500-625	500-625	500-625
	53	Weight	Minimum / Maximum	lb (kg)	1496.9/2204.6 (679/1000)	1496.9/2204.6 (679/1000)	1496.9/2204.6 (679/1000)
	54	Lead Length	Position A	in (mm)	39.4 (1000)	39.4 (1000)	39.4 (1000)
55	Connector		Type	DIN 320A 48V	DIN 320A 48V	DIN 320A 48V	

MAIN TRUCK SPECIFICATIONS - 3 WHEEL

CHARACTERISTICS	1	Manufacturer's Name		UniCarriers	UniCarriers	UniCarriers		
	2	Model	Model designation	MXST16-2	MXST18-2	MXST20-2		
	3	Rated Load Capacity		lb (kg)	3000 (1425)	3500 (1600)	4000 (1800)	
4	Load Center	Distance	in (mm)	23.6 (600)	23.6 (600)	23.6 (600)		
5	Power Type	Electric	voltage	Electric/48V	Electric/48V	Electric/48V		
6	Operator Orientation			Seated	Seated	Seated		
DIMENSIONS	7	Tire Type	Front & rear	Solid Pneu.SE	Solid Pneu.SE	Solid Pneu.SE		
	8	Wheels	Number - front/rear (x=driven)	2x/1	2x/1	2x/1		
	9	Mast	Maximum fork height	in (mm)	129.5 (3290)	129.5 (3290)	129.5 (3290)	
	10		Mast lowered (OHL)	in (mm)	83.7 (2125)	83.7 (2125)	83.7 (2125)	
	11		Mast extended with LBR	in (mm)	107.7 (4335)	170.7 (4335)	170.7 (4335)	
	12		Standard freelif	in (mm)	3.1 (80)	3.1 (80)	3.1 (80)	
	13	Forks	Thickness & width & Length	in (mm)	1.4x3.9x5.9 (35x100x1150)	1.4x3.9x5.9 (35x100x1150)	1.4x3.9x5.9 (35x100x1150)	
	14	Tilt Angle	Standard mast - fwd/back	degree	5/7.5	5/7.5	5/7.5	
	15	Overall Dimensions	Length (to face of forks)	in (mm)	76.9 (1954)	76.9 (1954)	77.5 (1969)	
	16		Width (standard tires)	in (mm)	42.9 (1090)	42.9 (1090)	44.9 (1140)	
	17		Height - top of OHG	in (mm)	80.7 (2050)	80.7 (2050)	80.7 (2050)	
	18		Height - top of standard LBR	in (mm)	48.0 (1220)	48.0 (1220)	48.0 (1220)	
	19		Width - standard carriage	in (mm)	36.2 (920)	36.2 (920)	36.2 (920)	
	20	Grade Clearance	Ramp breakover angle (with/without load)	%	3.7 (95)	3.7 (95)	3.7 (95)	
	21	Overhang	Front	in (mm)	13.5 (343)	13.5 (343)	13.5 (343)	
	22	Turning Radius	Minimum outside	in (mm)	63.4 (1610)	63.4 (1610)	63.4 (1610)	
	23	Min Right Angle Stack	1000 x 1200 mm pallets, crosswise / 800 x 1200 mm pallets, lengthwise	in (mm)	129.1 (3281) / 134.0 (3404)	129.1 (3281) / 134.0 (3404)	129.7 (3295) / 134.6 (3419)	
	PERFORMANCE	24	Speed Maximum	Travel - loaded / unloaded	mph (km/h)	10.6 (16)	10.6 (16)	10.6 (16)
		25		Lift - loaded / unloaded	fpm (mm/sec)	0.52/0.62	0.46/0.62	0.42/0.62
26		Lowering - loaded / unloaded		fpm (mm/sec)	0.56/0.56	0.56/0.56	0.56/0.56	
27		Drawbar Pull Maximum	Full load	lb (N)	3350 (14900)	3350 (14900)	3327 (14800)	
28	Gradeability Maximum	Full load (with/without load)	%	27/35	26/35	24/35		
WEIGHT	29	Truck Weight	Empty, min. battery	lb (kg)	6501.4 (2949)	6876.2 (3119)	7367.8 (3342)	
	30	Weight Distribution	Full load front/rear - min. battery	lb (kg)	8862.6 (4020)/ 1166.3 (529)	9552.6 (4333)/ 1291.9 (586)	10518.3 (4711)/ 1391.1 (631)	
	31		No load front/rear - min. battery	lb (kg)	3254.0 (1476)/ 3249.6 (1474)	3243.0 (1471)/ 3635.4 (1649)	3326.7 (1509)/ 4041.1 (1833)	
CHASSIS & WHEELS	32	Tire Size	Front	in	18x7-8	18x7-8	200/50-10	
	33		Rear	in	140/55-9	140/55-9	140/55-9	
	34	Wheelbase		in (mm)	56.2 (1428)	56.2 (1428)	56.2 (1428)	
	35	Tread - Center of Tire	Front / rear (standard tires)	in (mm)	36.6/6.9 (930/174)	36.6/6.9 (930/174)	36.6/6.9 (930/174)	
	36	Headroom	SIP to bottom pf OHG	in (mm)	35.7 (908)	35.7 (908)	35.7 (908)	
	37	Counterweight Height		in (mm)	38.04 (966.36)	38.04 (966.36)	38.04 (966.36)	
	38	Step Height		in (mm)	16.0 (407)	16.0 (407)	16.0 (407)	
	39	Ground Clearance	Under mast	in (mm)	3.7 (95)	3.7 (95)	3.7 (95)	
	40		Under frame, center of wheelbase	in (mm)	3.7 (95)	3.7 (95)	3.7 (95)	
	41	Service Brake	Type		Electric	Electric	Electric	
	42	Parking Brake	Type		Magnetic	Magnetic	Magnetic	
43	Steering	On-demand		Electric	Electric	Electric		
DIN 320A 48V LINE	44	Traction Motor	Type / Rating (1-hour)	(kW)	AC / 2 x 5.5 kW	AC / 2 x 5.5 kW	AC / 2 x 5.5 kW	
	45		Control type		AC	AC	AC	
	46	Pump Motor	Type / Rating (5-minute)	(kW)	AC / 10 kW	AC / 10 kW	AC / 10 kW	
BATTERY	47	Battery Compartment Size	W x H - Maximum	in (mm)	W: 33.5 (850) with spacers W: 40.0 (1018) w/o spacers H: 26.0 (660) with battery rollers H: 27.2 (690) w/o battery rollers	W: 33.5 (850) with spacers W: 40.0 (1018) w/o spacers H: 26.0 (660) with battery rollers H: 27.2 (690) w/o battery rollers	W: 33.5 (850) with spacers W: 40.0 (1018) w/o spacers H: 26.0 (660) with battery rollers H: 27.2 (690) w/o battery rollers	
	48		L - Maximum	in (mm)	25.2 (640)	25.2 (640)	25.2 (640)	
	49	Recommended Battery Size	W x H - Maximum	in (mm)	W: 32.7 (830) with spacers W: 39.6 (1006) w/o spacers H: 24.7 (627)	W: 32.7 (830) with spacers W: 39.6 (1006) w/o spacers H: 24.7 (627)	W: 32.7 (830) with spacers W: 39.6 (1006) w/o spacers H: 24.7 (627)	
	50		L - Maximum	in (mm)	24.8 (630)	24.8 (630)	24.8 (630)	
	51		Lead acid	Type	Lead acid	Lead acid	Lead acid	
	52	Capacity	Minimum / Maximum	Ah/5h	625-750	625-750	625-750	
	53	Weight	Minimum / Maximum	lb (kg)	1790.1/2557.4 (812/1160)	1790.1/2557.4 (812/1160)	1790.1/2557.4 (812/1160)	
	54	Lead Length	Position A	in (mm)	39.4 (1000)	39.4 (1000)	39.4 (1000)	
	55	Connector		Type	DIN 320A 48V	DIN 320A 48V	DIN 320A 48V	



MAIN TRUCK SPECIFICATIONS - 4 WHEEL

CHARACTERISTICS	1	Manufacturer's Name		UniCarriers	UniCarriers	UniCarriers		
	2	Model	Model designation	MXS16C-2	MXS18C-2	MXS16-2		
	3	Rated Load Capacity		lb (kg)	3000 (1425)	3500 (1600)	3000 (1425)	
	4	Load Center	Distance	in (mm)	23.6 (600)	23.6 (600)	23.6 (600)	
	5	Power Type	Electric	voltage	Electric/48v	Electric/48V	Electric/48V	
	6	Operator Orientation			Seated	Seated	Seated	
DIMENSIONS	7	Tire Type	Front & rear		Solid Pneu. SE	Solid Pneu. SE	Solid Pneu. SE	
	8	Wheels	Number - front/rear (x=driven)		2x/2	2x/2	2x/2	
	9	Mast	Maximum fork height	in (mm)	129.5 (3290)	129.5 (3290)	129.5 (3290)	
	10		Mast lowered (OHL)	in (mm)	83.7 (2125)	83.7 (2125)	83.7 (2125)	
	11		Mast extended with LBR	in (mm)	170.7 (4335)	170.7 (4335)	170.7 (4335)	
	12		Standard freelif	in (mm)	3.1 (80)	3.1 (80)	3.1 (80)	
	13	Forks	Thickness & width & Length		in (mm)	1.4x3.9x45.3 (35x100x1150)	1.4x3.9x45.3 (35x100x1150)	1.4x3.9x45.3 (35x100x1150)
	14	Tilt Angle	Standard mast - fwd/back		degree	5/7.5	5/7.5	5/7.5
	15	Overall Dimensions	Length (to face of forks)	in (mm)	78.8 (2002)	78.8 (2002)	83.1 (2110)	
	16		Width (standard tires)	in (mm)	42.9 (1090)	42.9 (1090)	42.9 (1090)	
	17		Height - top of OHG	in (mm)	80.7 (2050)	80.7 (2050)	80.7 (2050)	
	18		Height - top of standard LBR	in (mm)	48.0 (1220)	48.0 (1220)	48.0 (1220)	
	19		Width - standard carriage	in (mm)	36.2 (920)	36.2 (920)	36.2 (920)	
	20	Grade Clearance	Ramp breakover angle (with/without load)		%	3.7 (95)	3.7 (95)	3.7 (95)
21	Overhang	Front	in (mm)	13.5 (343)	13.5 (343)	13.5 (343)		
22	Turning Radius	Minimum outside		in (mm)	65.4 (1662)	65.4 (1662)	69.7 (1770)	
23	Min Right Angle Stack	1000 x 1200 mm pallets, crosswise / 800 x 1200 mm pallets, lengthwise		in (mm)	131.2 (3333) / 136.0 (3456)	131.2 (3333) / 136.0 (3456)	135.5 (3441) / 140.3 (3564)	
PERFORMANCE	24	Speed Maximum	Travel - loaded / unloaded	mph (km/h)	11 (16)	11 (16)	11 (16)	
	25		Lift - loaded / unloaded	fpm (mm/sec)	108/122 (.55/.62)	102/122 (.52/.62)	90/122 (.46/.62)	
	26		Lowering - loaded / unloaded	fpm (mm/sec)	110 (.56/.56)	110 (.56/.56)	110 (.56/.56)	
	27	Drawbar Pull Maximum	Full load	lb (N)	3350 (14900)	3350 (14900)	3372 (15000)	
28	Gradeability Maximum	Full load (with/without load)		%	27/35	26/35	27/35	
WEIGHT	29	Truck Weight	Empty, min. battery		lb (kg)	6490.4 (2944)	6865.2 (3114)	6519.1 (2957)
	30	Weight Distribution	Full load front/rear - min. battery		lb (kg)	8796.4 (3990)/ 1221.4 (554)	9504.1 (4311)/ 1329.4 (603)	8836.1 (4008)/ 1212.5 (550)
	31		No load front/rear - min. battery		lb (kg)	3135.0 (1422)/ 3355.4 (1522)	3135.0 (1422)/ 3730.2 (1692)	3329.0 (1510)/ 3192.3 (1448)
CHASSIS & WHEELS	32	Tire Size	Front	in	18x7-8	18x7-8	18x7-8	
	33		Rear	in	16x6-8	16x6-8	16x6-8	
	34	Wheelbase			in (mm)	54.9 (1394)	54.9 (1394)	59.1 (1502)
	35	Tread - Center of Tire	Front / rear (standard tires)		in (mm)	36.6/35.4 (930/898)	36.6/35.4 (930/898)	36.6/35.4 (930/898)
	36	Headroom	SIP to bottom pf OHG		in (mm)	35.7 (908)	35.7 (908)	35.7 (908)
	37	Counterweight Height			in (mm)	38.04 (966.36)	38.04 (966.36)	38.04 (966.36)
	38	Step Height			in (mm)	16.0 (407)	16.0 (407)	16.0 (407)
	39	Ground Clearance	Under mast		in (mm)	3.7 (95)	3.7 (95)	3.7 (95)
	40		Under frame, center of wheelbase		in (mm)	3.7 (95)	3.7 (95)	3.7 (95)
	41	Service Brake	Type			Electric	Electric	Electric
42	Parking Brake	Type			Magnetic	Magnetic	Magnetic	
43	Steering	On-demand			Electric	Electric	Electric	
DIN 320A 48V LINE	44	Traction Motor	Type / Rating (1-hour)	(kW)	AC / 2 x 5.5 kW	AC / 2 x 5.5 kW	AC / 2 x 5.5 kW	
	45		Control type			AC	AC	AC
	46	Pump Motor	Type / Rating (5-minute)	(kW)	AC / 10 kW	AC / 10 kW	AC / 10 kW	
BATTERY	47	Battery Compartment Size	W x H - Maximum	in (mm)	W: 33.5 (850) with spacers W: 40.0 (1018) w/o spacers H: 26.0 (660) with battery rollers H: 27.2 (690) w/o battery rollers	W: 33.5 (850) with spacers W: 40.0 (1018) w/o spacers H: 26.0 (660) with battery rollers H: 27.2 (690) w/o battery rollers	W: 33.5 (850) with spacers W: 40.0 (1018) w/o spacers H: 26.0 (660) with battery rollers H: 27.2 (690) w/o battery rollers	
	48		L - Maximum	in (mm)	20.9 (532)	20.9 (532)	25.2 (640)	
	49	Recommended Battery Size	W x H - Maximum	in (mm)	W: 32.7 (830) with spacers W: 39.6 (1006) w/o spacers H: 24.7 (627)	W: 32.7 (830) with spacers W: 39.6 (1006) w/o spacers H: 24.7 (627)	W: 32.7 (830) with spacers W: 39.6 (1006) w/o spacers H: 24.7 (627)	
	50		L - Maximum	in (mm)	20.6 (522)	20.6 (522)	24.8 (630)	
	51		Lead acid	Type		Lead acid	Lead acid	Lead acid
	52	Capacity	Minimum / Maximum		Ah/5h	500-625	500-625	625-750
	53	Weight	Minimum / Maximum		lb (kg)	1496.9/2204.6 (679/1000)	1496.9/2204.6 (679/1000)	1496.9/2557.4 (681/1160)
	54	Lead Length	Position A		in (mm)	39.4 (1000)	39.4 (1000)	39.4 (1000)

**MAIN TRUCK SPECIFICATIONS - 4 WHEEL**

CHARACTERISTICS	1	Manufacturer's Name		<b>UniCarriers</b>	<b>UniCarriers</b>
	2	Model	Model designation	<b>MXS18-2</b>	<b>MXS20-2</b>
	3	Rated Load Capacity		3500 (1600)	4000 (1800)
	4	Load Center	Distance	in (mm)	23.6 (600)
	5	Power Type	Electric	voltage	Electric/48V
	6	Operator Orientation		Seated	Seated
DIMENSIONS	7	Tire Type	Front & rear	Solid Pneu. SE	Solid Pneu. SE
	8	Wheels	Number - front/rear (x=driven)	2x/2	2x/2
	9	Mast	Maximum fork height	in (mm)	129.5 (3290)
	10		Mast lowered (OHL)	in (mm)	83.7 (2125)
	11		Mast extended with LBR	in (mm)	170.7 (4335)
	12		Standard freelif	in (mm)	3.1 (80)
	13	Forks	Thickness & width & Length	in (mm)	1.4x3.9x45.3 (35x100x1150)
	14	Tilt Angle	Standard mast - fwd/back	degree	5/7.5
	15	Overall Dimensions	Length (to face of forks)	in (mm)	83.1 (2110)
	16		Width (standard tires)	in (mm)	42.9 (1090)
	17		Height - top of OHG	in (mm)	80.7 (2050)
	18		Height - top of standard LBR	in (mm)	48.0 (1220)
	19		Width - standard carriage	in (mm)	36.2 (920)
	20	Grade Clearance	Ramp breakover angle (with/without load)	%	4 (95)
21	Overhang	Front	in (mm)	13.5 (343)	
22	Turning Radius	Minimum outside	in (mm)	69.7 (1770)	
23	Min Right Angle Stack	1000 x 1200 mm pallets, crosswise / 800 x 1200 mm pallets, lengthwise	in (mm)	135.5 (3441) / 140.3 (3564)	
PERFORMANCE	24	Speed Maximum	Travel - loaded / unloaded	mph (km/h)	11 (16)
	25		Lift - loaded / unloaded	fpm (mm/sec)	102/122 (.52/.62)
	26		Lowering - loaded / unloaded	fpm (mm/sec)	110 (.56/.56)
	27	Drawbar Pull Maximum	Full load	lb (N)	3350 (14900)
28	Gradeability Maximum	Full load (with/without load)	%	26/35	
WEIGHT	29	Truck Weight	Empty, min. battery	lb (kg)	6827.7 (3097)
	30	Weight Distribution	Full load front/rear - min. battery	lb (kg)	9468.9 (4295)/ 1329.4 (603)
	31		No load front/rear - min. battery	lb (kg)	3271.7 (1484)/ 3556.1 (1613)
CHASSIS & WHEELS	32	Tire Size	Front	in	18x7-8
	33		Rear	in	16x6-8
	34	Wheelbase		in (mm)	59.1 (1502)
	35	Tread - Center of Tire	Front / rear (standard tires)	in (mm)	36.6/35.4 (930/898)
	36	Headroom	SIP to bottom pf OHG	in (mm)	35.7 (908)
	37	Counterweight Height		in (mm)	38.04 (966,36)
	38	Step Height		in (mm)	16.0 (407)
	39	Ground Clearance	Under mast	in (mm)	3.7 (95)
	40		Under frame, center of wheelbase	in (mm)	3.7 (95)
	41	Service Brake	Type		Electric
42	Parking Brake	Type		Magnetic	
43	Steering	On-demand		Electric	
DIN 320A 48V LINE	44	Traction Motor	Type / Rating (1-hour)	(kW)	AC / 2 x 5.5 kW
	45		Control type		AC
	46	Pump Motor	Type / Rating (5-minute)	(kW)	AC / 10 kW
BATTERY	47	Battery Compartment Size	W x H - Maximum	in (mm)	W: 33.5 (850) with spacers W: 40.0 (1018) w/o spacers H: 26.0 (660) with battery rollers H: 27.2 (690) w/o battery rollers
	48		L - Maximum	in (mm)	25.2 (640)
	49	Recommended Battery Size	W x H - Maximum	in (mm)	W: 32.7 (830) with spacers W: 39.6 (1006) w/o spacers H: 24.7 (627)
	50		L - Maximum	in (mm)	24.8 (630)
	51		Lead acid	Type	Lead acid
	52	Capacity	Minimum / Maximum	Ah/5h	625-750
	53	Weight	Minimum / Maximum	lb (kg)	1790.2/2557.4 (812/1160)
	54	Lead Length	Position A	in (mm)	39.4 (1000)

STANDARD MAST SPECIFICATIONS AND RATED CAPACITIES - 3 WHEEL

Mast Type	Maximum Fork Height	Overall Height		Free Lift	Tilt Angle Fwd/Bkwd	Rated Capacity at 24" (600) Load Center					
		Lowered	Fully Extended			MXST14-2	MXST16C-2	MXST18C-2	MXST16-2	MXST18-2	MXST20-2
	MFH	OHL	With LBR	With LBR	lb (kg)	lb (kg)	lb (kg)	lb (kg)	lb (kg)	lb (kg)	
	in (mm)	in (mm)	in (mm)	in (mm)	degrees	lb (kg)	lb (kg)	lb (kg)	lb (kg)	lb (kg)	
SIMPLEX	119.9 (3045)	58.2 (1480)	78.7 (2000)	3.1 (80)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	141.9 (3605)	69.2 (1760)	100.7 (2560)	3.1 (80)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	149.8 (3805)	73.2 (1860)	108.6 (2760)	3.1 (80)	5/7.5	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	159.3 (4045)	77.9 (1980)	118.1 (3000)	3.1 (80)	5/7.5	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	170.7 (4335)	83.7 (2125)	129.5 (3290)	3.1 (80)	5/7.5	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	180.1 (4575)	88.4 (2245)	138.9 (3530)	3.1 (80)	5/7.5	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	187.6 (4765)	93.9 (2385)	146.5 (3720)	3.1 (80)	5/7.5	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	202.2 (5135)	101.2 (2570)	161.0 (4090)	3.1 (80)	5/7.5	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	217.5 (5525)	109.3 (2775)	176.4 (4480)	3.1 (80)	5/5	2701 (1225.2)	3086 (1399.8)	3472 (1574.9)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	238.0 (6045)	119.5 (3035)	196.9 (5000)	3.1 (80)	5/5	2590 (1174.8)	2976 (1349.9)	3362 (1525.0)	3031 (1374.8)	3472 (1574.9)	3858 (1750.0)
	257.7 (6545)	129.3 (3285)	216.5 (5500)	3.1 (80)	5/3.5	2480 (1124.9)	2866 (1300.0)	3252 (1475.1)	2921 (1324.9)	3307 (1500.0)	3748 (1700.1)
	277.4 (7045)	139.2 (3535)	236.2 (6000)	3.1 (80)	5/3.5	2425 (1100.0)	2756 (1250.1)	3142 (1425.2)	2811 (1275.0)	3197 (1450.1)	3582 (1624.8)
DUPLEX	151.4 (3845)	74.0 (1880)	110.2 (2800)	32.9 (835)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	159.3 (4045)	77.9 (1980)	118.1 (3000)	36.8 (935)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	170.9 (4340)	83.7 (2125)	129.7 (3295)	42.5 (1080)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	179.5 (4560)	88.4 (2245)	138.3 (3515)	47.2 (1200)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	186.8 (4745)	93.9 (2385)	145.7 (3700)	52.8 (1340)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	199.8 (5075)	101.2 (2570)	158.7 (4030)	60.0 (1525)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
TRIPLEX	187.2 (4755)	70.0 (1780)	146.1 (3710)	28.9 (735)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	199.0 (5055)	74.0 (1880)	157.9 (4010)	32.9 (835)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	210.8 (5355)	77.9 (1980)	169.7 (4310)	36.8 (935)	5/6	2756 (1250.1)	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	228.1 (5795)	83.7 (2125)	187.0 (4750)	42.5 (1080)	5/6	2646 (1200.2)	3031 (1374.8)	3417 (1549.9)	3086 (1399.8)	2472 (1174.9)	3913 (1774.9)
	241.5 (6135)	88.4 (2245)	200.4 (5090)	47.2 (1200)	5/3.5	2590 (1174.8)	2921 (1324.9)	3307 (1500.0)	3086 (1399.8)	3417 (1549.9)	3803 (1725.0)
	257.3 (6535)	93.9 (2385)	216.1 (5490)	52.8 (1340)	5/3.5	2480 (1124.9)	2866 (1300.0)	3197 (1450.1)	2976 (1349.9)	3307 (1500.0)	3693 (1675.1)
	277.0 (7035)	101.2 (2570)	235.8 (5990)	60.0 (1525)	5/3.5	2370 (1075.0)	2756 (1250.1)	3086 (1399.8)	2811 (1275.0)	3197 (1450.1)	3582 (1642.8)
	296.7 (7535)	111.4 (2830)	255.5 (6490)	70.3 (1785)	5/3.5	2260 (1025.1)	2646 (1200.2)	2976 (1349.9)	2701 (1225.2)	2976 (1349.9)	3417 (1549.9)
	316.7 (8045)	119.5 (3035)	275.6 (7000)	78.3 (1990)	5/3.5	2149 (974.8)	2315 (1050.1)	2315 (1050.1)	2315 (1050.1)	2315 (1050.1)	2535 (1149.9)

Note: Rated load capacity is for reference only. Actual capacity will vary depending on trucks final configuration.

STANDARD MAST SPECIFICATIONS AND RATED CAPACITIES - 4 WHEEL

Mast Type	Maximum Fork Height	Overall Height		Free Lift	Tilt Angle Fwd/Bkwd	Rated Capacity at 24" (600) Load Center				
		Lowered	Fully Extended			MXS16C-2	MXS18C-2	MXS16-2	MXS18-2	MXS20-2
	MFH	OHL	With LBR	With LBR	lb (kg)	lb (kg)	lb (kg)	lb (kg)	lb (kg)	
	in (mm)	in (mm)	in (mm)	in (mm)	degrees	lb (kg)	lb (kg)	lb (kg)	lb (kg)	lb (kg)
SIMPLEX	119.9 (3045)	58.2 (1480)	78.7 (2000)	3.1 (80)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	141.9 (3605)	69.2 (1760)	100.7 (2560)	3.1 (80)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	149.8 (3805)	73.2 (1860)	108.6 (2760)	3.1 (80)	5/7.5	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	159.3 (4045)	77.9 (1980)	118.1 (3000)	3.1 (80)	5/7.5	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	170.7 (4335)	83.7 (2125)	129.5 (3290)	3.1 (80)	5/7.5	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	180.1 (4575)	88.4 (2245)	138.9 (3530)	3.1 (80)	5/7.5	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	187.6 (4765)	93.9 (2385)	146.5 (3720)	3.1 (80)	5/7.5	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	202.2 (5135)	101.2 (2570)	161.0 (4090)	3.1 (80)	5/7.5	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	217.5 (5525)	109.3 (2775)	176.4 (4480)	3.1 (80)	5/5	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	238.0 (6045)	119.5 (3035)	196.9 (5000)	3.1 (80)	5/5	3086 (1399.8)	3472 (1574.9)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	257.7 (6545)	129.3 (3285)	216.5 (5500)	3.1 (80)	5/3.5	2976 (1349.9)	3362 (1525.0)	3086 (1399.8)	3472 (1574.9)	3803 (1725.0)
	277.4 (7045)	139.2 (3535)	236.2 (6000)	3.1 (80)	5/3.5	2701 (1225.2)	2701 (1225.2)	2976 (1349.9)	2976 (1349.9)	3693 (1675.1)
DUPLEX	151.4 (3845)	74.0 (1880)	110.2 (2800)	32.9 (835)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	159.3 (4045)	77.9 (1980)	118.1 (3000)	36.8 (935)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	170.9 (4340)	83.7 (2125)	129.7 (3295)	42.5 (1080)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	179.5 (4560)	88.4 (2245)	138.3 (3515)	47.2 (1200)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	186.8 (4745)	93.9 (2385)	145.7 (3700)	52.8 (1340)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	199.8 (5075)	101.2 (2570)	158.6 (4030)	60.0 (1525)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
TRIPLEX	187.2 (4755)	70.0 (1780)	146.1 (3710)	28.9 (735)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	199.0 (5055)	74.0 (1880)	157.9 (4010)	32.9 (835)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	210.8 (5355)	77.9 (1980)	169.7 (4310)	36.8 (935)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	228.1 (5795)	83.7 (2125)	187.0 (4750)	42.5 (1080)	5/6	3142 (1425.2)	3527 (1599.8)	3142 (1425.2)	3527 (1599.8)	3968 (1799.9)
	241.5 (6135)	88.4 (2245)	200.4 (5090)	47.2 (1200)	5/3.5	3031 (1374.8)	3417 (1549.9)	3142 (1425.2)	3527 (1599.8)	3913 (1774.9)
	257.3 (6535)	93.9 (2385)	216.1 (5490)	52.8 (1340)	5/3.5	2921 (1324.9)	3307 (1500.0)	3031 (1374.8)	3417 (1549.9)	3803 (1725.0)
	277.0 (7035)	101.2 (2570)	235.8 (5990)	60.0 (1525)	5/3.5	2811 (1275.0)	3197 (1450.1)	2921 (1324.9)	3307 (1500.0)	3638 (1650.2)
	296.7 (7535)	111.4 (2830)	255.5 (6490)	70.3 (1785)	5/3.5	2701 (1225.2)	3086 (1399.8)	2811 (1275.0)	3086 (1399.8)	3527 (1599.8)
	316.7 (8045)	119.5 (3035)	275.6 (7000)	78.3 (1990)	5/3.5	2370 (1075.0)	2370 (1075.0)	2370 (1075.0)	2370 (1075.0)	2480 (1124.9)

Note: Rated load capacity is for reference only. Actual capacity will vary depending on trucks final configuration.

## ERGONOMICS & COMFORT

The MXS Series offers a variety of operator conveniences including a 360° steering option that provides greater turning agility. This allows the truck to turn and move in the opposite direction without stopping and avoids destabilizing the load (3-wheel model).

Sized to fit a wide range of drivers, the spacious operator compartment offers comfort and easy access features. An extended seat and steering column adjustability assure a comfortable driving position and enable good vision. The Inclined and narrow dashboard, compact and open design steering wheel and optimized free lift cylinder structure help to provide excellent forward, downward and side visibility. Easy-to-read multi-function color display encourages correct use and maintenance of truck. Fingertip hydraulic controls on adjustable armrest (optional) are spring-force-optimized to ensure ergonomic hand positioning, anatomical support and free movement. Low-noise gearbox improves conditions for drivers and their colleagues. And pedal design, position and angles helps reduce fatigue for a wide range of operator sizes.

The passive sway control keeps automatic parking brake open during lifts, so mast sway energy can be absorbed by the chassis. Electromagnetic parking brakes eliminate the need for levers or pedals to release or activate the brakes. Plus, the Steering knob automatically returns to convenient 8 o'clock position when truck drives straight, even if the wheel has been overturned. Finally, our Presence Detection System+ includes automatic parking brake, hill hold and – if operator is not seated – and the prevention of travel and hydraulic movement.

## EFFICIENCY & CONTROL

The MXS Series offers advanced features that make driving and load handling easy, steady and comfortable. Sized to fit a wide range of drivers.

Efficient motors with a high RPM range give better precision in acceleration control, create more torque at low speeds and reduce energy consumption. The Responsive Drive System (RDS) reacts instantly to changes in the speed of foot and pedal movement to help assist with smooth controlled actions including cornering, stops and starts. The variable steering ratio and steering force are continuously optimized for different travel speeds. Advanced curve control coordinates the two front-wheel drive motors and rear steer axle motor to optimize turning speed, stabilize fast sideways movements of the counterweight, and prevent tilting when straightening after high-speed turns.

As standard, truck acceleration and hydraulic performance is automatically limited at lifts from 138 in./3.5m for steady, controlled handling. This feature can be set to activate at lifts above 79 in./2m as an option.

## LOWER OPERATING COSTS

Robust construction and sealed components mean you can save money on maintenance needs.

Fast battery compartment access speeds up servicing and exchanges. Easy-to-read multi-function color display encourages correct use and maintenance of truck. Modular design simplifies addition or replacement of parts, including overhead guard and cabin options.

## LITHIUM-ION BATTERIES

Smart power solutions designed to communicate directly with the truck for increased efficiency and results. Maintenance free which reduces total cost of ownership and downtime from traditional lead acid batteries.

Li-Ion batteries are covered by a 6-year, 3,600 cycles with 75% residual capacity guarantee.

## EFFICIENT PERFORMANCE & GREATER UPTIME

To maintain precise control, load-sensing hydraulic system automatically adjusts to the weight being handled. Passive sway control keeps the automatic parking brake open so mast sway energy is absorbed by the mass of the whole truck. All masts and low-friction side-shift minimize sway, twisting and noise.

Fully electronic magnetic brakes require less servicing and offer greater energy efficiency. Simultaneous hydraulic functions are electronically compensated (when using the optional fingertip control) to keep their behavior consistent whatever the load weight.

Pre-set ECO and PRO modes can be selected for different drivers and tasks, or customized settings can be applied by service engineers.

## RUGGED & DURABLE

Durable hose and hydraulic cylinder sealing specification withstands high temperature range, weathering and physical wear.

## STANDARD EQUIPMENT

- Efficient motors with high RPM range
- Fully electronic magnetic brakes
- Robust construction and sealed components
- Adjustable full suspension vinyl seat
- Fast battery compartment access
- Easy-to-read multi-function color display
- Modular design
- Responsive Drive System (RDS)
- Advanced curve control coordinates
- Dual drive '4-wheel steering' with a +100° rear turning axle
- LED front and rear working lights
- Truck acceleration and hydraulic performance is automatically limited at lifts from 138 in./3.5m
- High-specification masts
- Pre-set ECO and PRO modes can be selected for different drivers and tasks
- Electromagnetic parking brakes
- 360° steering option (3 wheel)\*

## OPTIONAL EQUIPMENT

- Simultaneous hydraulic functions are electronically compensated
- Pre-set ECO and PRO modes can be customized to allow settings to be applied by service engineers
- Truck acceleration and hydraulic performance is automatically limited at lifts above 79 in./2m

\* Needs to be activated via software (TruckTool).

Note: Equipping this model (these models) with a power source (e.g., Lithium-Ion, Hydrogen Full cells, etc.) that has not been approved by the factory is considered a modification. Per OSHA 1910.178 and ANSI/ITSDF B56.1, please consult with your factory representative prior to installing any non-OEM power source that has not been previously approved.

## Reliability.

It's the defining trait of our company and our forklifts.



UniCarriers Forklift's roots extend back over 100 years, and over that time, strong, reliable performance has always been the hallmark of our organization, our people and our equipment.

Today, our unrivaled reliability continues to provide UniCarriers Forklift's customers with a competitive edge. And together, we move the merchandise that moves world commerce with greater efficiency, economy and reliability.

When it comes to providing forklifts that make a difference for our customers and theirs...

## We Never Quit.

**UNI CARRIERS**<sup>®</sup>  
[ **FORKLIFT** ]

[LogisnextAmericas.com/UniCarriers](https://LogisnextAmericas.com/UniCarriers)

SB-MXS-09-2023 Printed in U.S.A.

© 2023 Mitsubishi Logisnext Americas Inc. UniCarriers® is a registered trademark of Mitsubishi Logisnext Co., Ltd. Mitsubishi Logisnext Americas Inc. reserves the right to make product changes relating to colors, equipment, specifications or available options without notice. For more information, contact your UniCarriers Forklift representative.

